OBOLAND COMMUNICATIONS

Specifications

RS-232 Remote Control Option and Remote Status Query

Ordering No.: **opt 51**

(Standard Feature on DHD model series)

Features:

- Remote Control of LCD Monitor Functions
- Available for Most 10" and Larger Monitors
- Standard RS-232 Format
- Interfaces wih all popular control systems



Option 51 used on Model dvi 19c

Comm Format: Baud Rate: Bits per word: Stop Bits: Connector: Pinout: Function Control & Query:	RS-232 Serial Communications 2400 bps (higher/selectabel in some models after 2009) 8 Bits 1 Bit, No Parity. DB9 Female or, 3.5mm (1/8") jack (varies by model) 2=Tx, 3=Rx, 5=Gnd (DB-9), or Tip=Rx, Ring=Tx, Sleeve=Gnd (3.5 mm) Brightness, Contrast, Color, Tint (all menu functions) H&V Position, H&V Size Scaling Modes, Orientation, Freeze, Rotate Menu OSD size, position, transparency, useage functions Input select, priority, system, and type PiP functions Zoom and Scalar functions Control circuit valid Auto Setup, Calibration User Menu Button Selections & Movements Soft Power On/Off (Remote Control stays awake) Volume (when installed)
Query-only Functions:	Input port status Average Picture Level

Specifications are subject to change without notice. 29 Jul 09